



MP5600

Feature

TFT Display : 3 inch, 320 x 240 resolution, display the colourful interface and personal photo

Professional Time Attendance Function : SMS, Schedule Bell

Card Integration : Proximity, Smart Card, HID Proximity and HID iClass

MP5600



Specification :

- LCD : 3" TFT Colour LCD
- Finger Capacity : 10.000 templates
- Log Buffer : 100.000 logs
- Card Capacity : 3.000 (optional)
- Authentication mode :
 - 1:1 (Fingerprint only)
 - 1:N (ID + Fingerprint)
 - ID + Password
 - Fingerprint & Password
- Function Key : 4 (Direct Press)
- Keypad : 16 Keypad, Alphabet & Numeric Keypad
- Communication :
 - RS 232
 - RS 485
 - TCP / IP
 - Modem (Optional)
- Identification speed
 - (1:N) Time : 1,4 seconds
- Verification
 - (1:1) Time : 1 seconds
- Sensor : Coated or Uncoated Optical
- USB : Support USB 2.0, Data Encrypted
- FAR : < 0,0001 %
- FRR : < 1 %
- LED : Red, Green
- Power Operating : 5 V / 400 mA
- Operating Temperature : 0 C - 45 C
- Operating Humidity : 20% - 80%
- Authentication : CE, FCC

HIT Corporation

Gandaria 8 Office Tower 7th floor, Unit IJ, Jl. Sultan Iskandar Muda, Kebayoran Lama, Jakarta Selatan 12240 – Indonesia

Phone: +62 21 2903 6581

Fax: +62 21 2903 6582

www.hitcorporation.com